

Humitest for biomass

The moisture meter for wood chips, barks, vegetable pellets, wood shavings, sawdust and miscanthus.



- Measures from 5 to 60% of water content
- Precise measures on site within seconds
- Menus in French, English, German Spanish, Italian and Russian

TECHNICAL FEATURES

Weight (g) with batteries	5.300 g
Dimensions (L x W x H in mm)	490 x 290 x 300
Batteries	4 X 1.5V (AA)
Display	LCD screen with back lighting Resolution: 0,1% humidity, 0,5°C température
Auto switch off	After 6 minutes
Presentation	Carton

MOISTURE METER MODE

Calibration	Wood chips, barks, vegetable pellets, wood shavings, sawdust and miscanthus 5 to 60 % (+/-1.5%) of wet mass water content depending on material measured Automatic correction depending on temperature
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 60°C (-4°F to 140°F)
Sample	13 litres

SUPPLIED ACCESSORIES

13-litre plastic bucket

OPTIONNAL ACCESSORIES

Digital scale 10.000 g

Density kit

Factory calibration certificate

WARRANTY AND STANDARDS

Standards/ certifications	CE, reference to the following standard: CEN/TS 14961:2005
Warranty	2 years

FIELDS OF APPLICATION

BIOENERGY

NEW! HUMITEST FOR BIOMASS PLUS

- Create specific calibrations
- Record and transfer measures to a PC
- Send measures and averages to a portable printer (in option)

The Humitest for Biomass can measure quickly and precisely different kinds of biomass.

